



0.37 kw Multistage Centrifugal Pump , Multiple Stage Centrifugal Pump

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: horizontal-slurrypump.com
- Certification: CE,CCC,UL
- Model Number: OEM
- Minimum Order Quantity: Negotiation
- Price: Negotiation
- Delivery Time: 5-8 work days
- Payment Terms: L/C, T/T
- Supply Ability: 100000 pcs per month



Product Specification

- Model: CDL2
- Power: 0.37-3kw
- Speed: 2900 Rpm
- Voltage: 50HZ
- Rated Current: 0.8/1.2/1.6/2/2.4/3/3.4
- Weight: 20-52 Kg
- Highlight: **light vertical multistage centrifugal pump**

for more products please visit us on horizontal-slurrypump.com

Product Description

CDL series Vertical Multistage Centrifugal Pump 0.37-3 kw for water supply and water treatment

CDL(T) is a non-self-priming vertical multi-stage centrifugal pump with a standard motor. The motor shaft and the pump shaft are directly connected with a coupling. The outer cylinder and the flow parts are fixed between the bracket and the inlet and outlet of the water body with nuts on the tie rod.

The pump can be equipped with intelligent protector according to the need, which can effectively protect the dry running, phase loss and overload of the pump

Model	Size(mm)					Weight(kg)
	B1	B2	B1+B2	D1	D2	
CDL2-20	258	210	468	148	117	20
CDL2-30	276	210	468	148	117	20
CDL2-40	294	210	504	148	117	22
CDL2-50	312	210	522	148	117	23
CDL2-60	340	245	585	170	142	26
CDL2-70	358	245	603	170	142	26
CDL2-90	394	245	639	170	142	28
CDL2-110	430	245	675	170	142	29
CDL2-130	476	290	766	190	155	35
CDL2-150	512	290	802	190	155	36
CDL2-180	566	290	856	190	155	41
CDL2-220	638	290	928	190	155	42
CDL2-260	720	315	1035	197	165	52

Model	Power(kw)	Q(m ³ /h)	0.8	1.2	1.6	2.0	2.4	3.0	3.4
CDL2-20	0.37	H(m)	18.5	17	16	15	13.3	11	8.5
CDL2-30	0.37		28	26	24	22	20	16.5	13
CDL2-40	0.55		37	35	33	30	26.5	22	17.5
CDL2-50	0.55		45.5	43	40	37	33	27	21.5
CDL2-60	0.75		54.5	52	49	45	40	33	26
CDL2-70	0.75		64	61	57	52	47	38	30.5
CDL2-90	1.1		82	78	73	67	60.5	49.5	39
CDL2-110	1.1		100	95	89	82	73	59	47
CDL2-130	1.5		119	114	106	98	88	71	55.5
CDL2-150	1.5		137	130	122	112	101	82	64.5
CDL2-180	2.2		166	157	148	148	122	100	80
CDL2-220	2.2		200	192	180	180	149	121	98
CDL2-260	3		239	228	214	214	179	145	116

Main Features

- 1) simple pump structure, simple installation and convenient maintenance.
- 2) 100% copper coil is used to ensure the service life of the motor.
- 3) extensive application, which can be widely used in life, industry, agriculture and other fields.
- 4) the use medium is clear water, clean, non-corrosive, non-explosive water and physical and chemical liquids.
- 5) the pump body has the advantages of stamping pump, standard impeller, small flow and high head.

FAQ

Q1. Can I have a sample order for water pump?

A: Yes, we welcome sample order to test and check quality. Mixed samples are acceptable.

Q2. What about the lead time?

A: Sample needs 3-5 days, mass production time needs 1-2 weeks for order quantity more than

Q3. Do you have any MOQ limit for water pump order?

A: Low MOQ, 1pc for sample checking is available

Q4. How do you ship the goods and how long does it take to arrive?

A: We usually ship by DHL, UPS, FedEx or TNT. It usually takes 3-5 days to arrive. Airline and sea shipping also optional.

Q5. How to proceed an order for water pump?

A: Firstly let us know your requirements or application.

Secondly We quote according to your requirements or our suggestions.

Thirdly customer confirms the samples and places deposit for formal order.

Fourthly We arrange the production.

 **ROMAN** Beijing Silk Road Enterprise Management Services Co.,LTD

 0086-17773109286

 jeffreyth@slurrypump.com

 horizontal-slurrypump.com

Floor 5, 2nd Building, Zhonglu Industrial Zone, Shenzhen City, Guangdong Province China (Mainland)