



Vertical Multistage Centrifugal Pump 1.5 - 15 Kw Industrial Liquid Conveying

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: horizontal-slurrypump.com
- Certification: CE,CCC,UL
- Model Number: OEM
- Minimum Order Quantity: Negotiation
- Price: Negotiation
- Delivery Time: 5-8 work days
- Payment Terms: L/C, T/T
- Supply Ability: 100000 pcs per month



Product Specification

- Model: CDL32
- Power: 1.5-15 Kw
- Rated Current: 16-40
- Voltage: 50 HZ
- Speed: 2900rpm
- Weight: 64/350 Kg
- Name: CDL Series Vertical Multistage Centrifugal Pump 1.5-15 Kw
- Highlight: **light vertical multistage centrifugal pump**

for more products please visit us on horizontal-slurrypump.com

Product Description

CDL series Vertical Multistage Centrifugal Pump 1.5-15 kw For Industrial liquid conveying

Pump instructions

CDL(T) is a non-self-priming vertical multi-stage centrifugal pump with a standard motor. The motor shaft and the pump shaft are directly connected with a coupling. The outer cylinder and the flow parts are fixed between the bracket and the inlet and outlet of the water body with nuts on the tie rod.

The pump can be equipped with intelligent protector according to the need, which can effectively protect the dry running, phase loss and overload of the pump.

Model	Size(mm)					Weight(kg)
	B1	B2	B1+B2	D1	D2	
CDL32-1	505	90	795	190	155	64/68
CDL32-2	575	315/335	890/910	197/230	165/180	77/85
CDL32-3	645	430	1075	260	208	100
CDL32-4	715	430	1145	260	208	109
CDL32-5	890	490	1380	330	255	181
CDL32-6	960	490	1450	330	255	185
CDL32-7	1030	490	1520	330	255	199
CDL32-8	1100	490	1590	330	255	203
CDL32-9	1170	550	1720	330	255	222
CDL32-10	1240	550	1790	330	255	227
CDL32-11	1310	590	1900	360	285	272
CDL32-12	1380	590	1970	360	285	276
CDL32-13	1450	660	2110	400	310	337
CDL32-14	1520	660	2180	400	310	341
CDL32-15	1590	660	2250	400	310	345
CDL32-16	1660	660	2320	400	310	350

Model	Power(kw)	Q(m ³ /h)	16	20	24	28	32	36	40
CDL32-1-1	1.5	H(m)	14	13	12	11	9	7	4
CDL32-1-2	2.2		18	17	15	14	13	11	8
CDL32-2-2	3		29	28	26	23	20	16	11
CDL32-2-4	4		36	34	32	29	27	23	18
CDL32-3-2	5.5		47	44	41	38	33	28	21
CDL32-3-5.5	5.5		54	51	48	44	40	35	27
CDL32-4-2	7.5		65	62	58	53	46	40	30
CDL32-4-7.5	7.5		72	69	65	59	53	47	37
CDL32-5-2	11		83	79	74	68	60	52	41
CDL32-5-11	11		90	86	81	74	67	59	47
CDL32-6-2	11		101	97	90	83	74	65	51
CDL32-6-11	11		108	104	97	90	81	72	57
CDL32-7-2	15		119	114	107	98	88	78	60
CDL32-7-15	15		126	121	113	105	95	85	67
CDL32-8-2	15		136	131	123	114	102	90	71
CDL32-8-15	15		144	138	130	120	109	97	77

Model	Power(kw)	Q(m ³ /h)	16	20	24	28	32	36	40
CDL32-9-2	18.5		154	148	140	129	117	102	82
CDL32-9-18.5	18.5		162	156	147	136	124	109	88
CDL32-10-2	18.5		175	166	157	146	131	115	91
CDL32-10-18.5	18.5		182	173	164	152	138	122	98
CDL32-11-2	22		193	184	173	164	146	128	102
CDL32-11-22	22		200	191	180	168	153	135	109

CDL32-12-2	22	H(m)	211	201	189	178	160	140	113
CDL32-12	22		218	208	196	184	167	147	120
CDL32-13-2	30		230	218	206	193	174	153	124
CDL32-13	30		237	225	213	200	181	160	131
CDL32-14-2	30		247	235	222	210	189	165	135
CDL32-14	30		255	242	229	216	196	172	142
CDL32-15-2	30		266	253	239	224	203	178	145
CDL32-15	30		274	260	246	231	210	185	152
CDL32-16-2	30		284	270	255	240	218	190	156
CDL32-16	30		292	277	262	246	225	197	163

CDL/CDLF are multi-functional products.

- 1). It can be used to convey various medium from tap water to industrial liquid at different temperature and with different flow rate and pressure. CDLF is applicable to convey non-corrosive liquid, while CDLF vertical inline multistage centrifugal pump is suitable for slightly corrosive liquid.
- 2). Water supply: Water filter and transport in Waterworks, boosting of main pipeline, boosting in high-rise buildings. Industrial boosting: Process flow water system, cleaning system, high-pressure washing system,
- 3). Fire fighting system.
- 4). Industrial liquid conveying: Cooling and air-conditioning, system, boiler water supply and condensing system, machine-associated purpose, acids and alkali.
- 5). Water treatment: Ultrafiltration system, reverse osmosis system, distillation system, separator, swimming pool.
- 6). Irrigation: Farmland irrigation, spray irrigation, dripping irrigation.



FAQ

Q1. Can I have a sample order for water pump?

A: Yes, we welcome sample order to test and check quality. Mixed samples are acceptable.

Q2. What about the lead time?

A: Sample needs 3-5 days, mass production time needs 1-2 weeks for order quantity more than

Q3. Do you have any MOQ limit for water pump order?

A: Low MOQ, 1pc for sample checking is available

Q4. How do you ship the goods and how long does it take to arrive?

A: We usually ship by DHL, UPS, FedEx or TNT. It usually takes 3-5 days to arrive. Airline and sea shipping also optional.

Q5. How to proceed an order for water pump?

A: Firstly let us know your requirements or application.


Secondly We quote according to your requirements or our suggestions.

Thirdly customer confirms the samples and places deposit for formal order.

Fourthly We arrange the production.

 **ROMAN Beijing Silk Road Enterprise Management Services Co.,LTD**

 0086-17773109286

 jeffreth@slurrypump.com

 horizontal-slurrypump.com

Floor 5, 2nd Building, Zhonglu Industrial Zone, Shenzhen City, Guangdong Province China (Mainland)